TOSHIBA

TEXTILE DESIGN



Highlights

A designer unit with an innovative textile concept A+++ for cooling & heating (10, 13) Dust filter, ozone air purifier and ultra-pure filter WiFi module integrated as standard

<u> </u>	
(R32	

A designer high-wall unit of the upper mid-range with a versatile textile cover concept, maximum energy efficiency, and a WiFi module integrated as standard. For use with 1:1 single outdoor unit or in combination with other indoor units on a 2- to 5-room multi outdoor unit.

Product advantages

- A flexible and adaptable textile concept
- Two fabric covers are included, another four are optional
- Very high energy efficiency (A++ to A+++)
- Direct current hybrid inverter technology
- Exceptionally high efficiency in the partial load range
- Whisper operating mode for indoor and outdoor units
- WiFi adapter integrated as standard
- Draft-free comfort: 3D airflow
- Intelligent airflow: Hada Careflow

Resource-friendly

- ECO mode
- Air used as energy source during heating operation
- Low GWP refrigerant R32

Clean ambient air

- Washable dust filter that covers the entire heat exchanger
- "Magic coil" coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after operation
- Highly-effective PM 2.5 μ ultra-pure filter
- Ozone air purifier with ionizer
- Optional active carbon-catechin filter strips (art. 818F0023)
- Optional IAQ filter strips (art. 818F0036)

Operation and features

- The infrared remote control included is designed for ease of use
- App control via smartphone or tablet as standard
- Smart speaker compatible with GOOGLE Assistant and AMAZON Alexa
- Weekly timer with 4 freely programmable settings per day
- 28 time programs per week
- Automatic mode
- Heating adjustable up to +30°C
- Hi Power, Power select
- QUIET operating mode for indoor unit
- SILENT operating mode for outdoor unit
- 3D airflow with 6 air flow patterns
- ECO operating mode
- 8°C frost protection function, fireplace mode
- Automatic restart after power blackout

WiFi special features

- One indoor unit can be controlled by up to 5 users
- Up to 10 indoor units can be controlled by one user
- Combine units in up to 3 groups/zones
- Indoor and outdoor temperature display
- Child lock function
- Multilingual app: can be set to DE, EN, CZ, HR, HU, SI, or SK



TOSHIBA

HAORI / SET

Indoor unit			RAS-B10N4KVRG-E
Outdoor unit			RAS-10J2AVSG-E1
Cooling capacity	kW	*	2,5
Cooling range (minmax.)	kW	*	0,89 - 3,20
Power consumption (min./nom./max.)	kW	*	0,19/0,54/0,79
Pdesign c	kW		2,5
Energy efficiency EER	W/W	*	4,63
Energy efficiency SEER		*	8,60
Energy efficiency class		*	A+++
Annual electricity consumption	kWh/a	*	102
Outdoor temperature operating range (minmax.)	°C	*	-15/+46
Heating capacity	kW	*	3,2
Heating range (minmax.)	kW	÷.	0,90 - 4,70
Power consumption (min./nom./max.)	kW	.	0,18/0,74/1,23
Pdesign h	kW		2,5
Energy efficiency COP	W/W	÷.	4,32
Energy efficiency SCOP		*	5,10
Energy efficiency class		*	A+++
Annual electricity consumption	kWh/a	۲	684
Outdoor temperature operating range (minmax.)	°C	*	-15/+24

		RAS-B10N4KVRG-E
dB(A)	*	19/-/41
dB(A)	*	19/-/41
dB(A)	*	54
dB(A)	۲	54
m³/h		300-600
mm		300 x 987 x 210
kg		11
	dB(A) dB(A) dB(A) m ³ /h mm	dB(A) dB(A) dB(A) dB(A) m³/h mm

🕸 Cooling 🔶 Heating

TOSHIBA

HAORI / SET

Outdoor unit			RAS-10J2AVSG-E1
Power supply	V/Ph+N/Hz		230/1/50
Recommended fusing	А		10
Sound pressure level (low/med/high)	dB(A)	*	-/-/44
Sound pressure level (low/med/high)	dB(A)	۲	-/-/46
Sound power level	dB(A)	*	-/-/57
ound power level	dB(A)	۲	-/-/59
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
iquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		20
leight difference (max.)	m		12
Airflow	m³/h		1890
Compressor type			Rotary
Refrigerant			R32
Refrigerant charge	kg		0,55
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
Neight	kg		26

🕸 Cooling 🔶 Heating

The measuring conditions for this product can be found at http://www.toshiba-klima.at/en/measuring-conditions.html

OSHIBA

TOSHIBA Features - general overview



Energy Label: Energy label A+ to A+++, indicates the power consumption and energy efficiency class.



ErP Ecodesign: All criteria of ECODESIGN-guideline are fulfilled and confirm highest system efficiency.



Hybrid inverter control: Smooth capacity regulation.



Rotary compressor: Reliability and high efficiency.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



R410A: Used refrigerant: R410A.



R32: Used refrigerant: R32.



Wifi ready: Optional control of the system via a smartphone.



KNX: Optional KNX bus connection.



Dust filter: Washable filter against coarse contamination.



IAQ filter: Fine mesh filter with natural substances.



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Plasma filter: Pure Mode: Electrostatic filter system.



Air ionizer: Negative iones cover polluted particles in the air. Dust, pollen and smoke are neutralized.



Self-cleaning function: Usage of condensate water for cleaning.



Auto Mode: Automatic selection between cooling and heating.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



Auto diagnostic: Check of system for flawless operation.



Eco Mode: Energy saving function.



Quiet Mode: Particularly low noise level - whispering mode.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



ব

Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



Floor Mode: Natural floor warming effect for greater comfort.



Preset Mode: Activates individual settings at the touch of a button.



One Touch Mode: Fully automatic operation adapted to your needs.



Timer: Individual programming of on-/off times.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Week Timer: Up to four settings per day and seven per week.



Automatic Restart: After a power blackout.



8 °C frost protection function: Frost protection for uninhabited rooms.



3D ~J||L> Louver: Flexible setting of louvers.



3D Airflow: 6 different airflow patterns in all directions.



