COMPACT ENTRY-LEVEL MODEL

Seiya – R32



Modern compact inverter A++ in cooling mode Infrared remote control included – WiFi ready



























Compact SEIYA entry-level high-wall unit with standard air filter. For use with 1:1 single outdoor unit or in combination with other indoor units on a 2- to 5-room multi outdoor unit.

\longrightarrow \mid

Product Advantages

- Excellent energy efficiency (A+ to A++)
- Colored, dimmable LED displays
- Eco operating mode
- Low GWP refrigerant R32
- Air used as energy source during heating operation
- Compact outdoor and indoor units
- "Quiet" whisper mode



Clean ambient air

- Washable dust filter that covers the entire heat exchanger
- "Dustless coil" coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after operation
- Optional active carbon-catechin filter strips (art.818F0023)

Easy operation

- Infrared remote control included
- WiFi ready
- Optional app control via smartphone or tablet
- OFF timer
- Automatic mode
- Hi Power
- Quiet mode
- Louver swing & fix
- Automatic restart after power blackout

\rightarrow

WiFi special features

- All indoor units & groups on/off control
- All indoor units & groups weekly timer
- All indoor units & groups setting
- Indoor temperature display
- Outdoor temperature display
- Quiet function
- Power select
- Child lock
- On/off timer
- 8°C functionECO operating mode
- Silence function for outdoor unit
- Fireplace operating mode
- Hi Power operating mode



TOSHIBA

Seiya – R32 / SET

Indoor unit			RAS-B16J2KVG-E
Outdoor unit			RAS-16J2AVG-E
Cooling capacity	kW	*	4,20
Cooling range (minmax.)	kW	*	1,20 - 4,70
Power consumption (min./nom./max.)	kW	*	0,32/1,40/1,80
Pdesign c	kW		4,20
Energy efficiency EER	W/W	*	3,00
Energy efficiency SEER		*	6,10
Energy efficiency class		*	A++
Annual electricity consumption	kWh/a	*	241
Outdoor temperature operating range (minmax.)	°C	*	-15/+46
Heating capacity	kW	*	5,00
Heating range (minmax.)	kW	*	1,30 - 6,00
Power consumption (min./nom./max.)	kW	*	0,24/1,40/1,70
Pdesign h	kW		3,60
Energy efficiency COP	W/W	*	3,57
Energy efficiency SCOP		*	4,00
Energy efficiency class		*	A+
Annual electricity consumption	kWh/a	*	1259
Outdoor temperature operating range (minmax.)	°C	*	-15/+24

Indoor unit			RAS-B16J2KVG-E
Sound pressure level (low/med/high)	dB(A)	*	22/35/43
Sound pressure level (low/med/high)	dB(A)	*	22/35/43
Sound power level	dB(A)	*	58
Sound power level	dB(A)	*	58
Airflow	m³/h		330 - 768
Condensate pipe diameter	mm		VP13
Dimensions (HxWxD)	mm		293 x 798 x 230
Weight	kg		9

* Cooling Heating

TOSHIBA

Seiya - R32 / SET

Outdoor unit			RAS-16J2AVG-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	А		13
Current consumption (max.)	А		9,0
Sound pressure level (low/med/high)	dB(A)	*	49
Sound pressure level (low/med/high)	dB(A)	*	52
Sound power level	dB(A)	*	64
Sound power level	dB(A)	*	66
Suction gas pipe diameter	mm (inch)		12,7 (1/2)
iquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		20
Height difference (max.)	m		12
Airflow	m³/h		2160
Compressor type			Rotary
Refrigerant			R32
Refrigerant charge	kg		0,62
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
	kg		30

* Cooling Heating

The measuring conditions for this product can be found at http://www.toshiba-klima.at/en/measuring-conditions.html

TOSHIBA

TOSHIBA Features - general overview



Energy Label: Energy label **A+ to A+++**, indicates the power consumption and energy efficiency class.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



ErP Ecodesign: All criteria of **ECODESIGN**-guideline are fulfilled and confirm highest system efficiency.



Auto diagnostic: Check of system for flawless operation.



Hybrid inverter control: Smooth capacity regulation.



Eco Mode: Energy saving function.



Rotary compressor: Reliability and high efficiency.



Quiet Mode: Particularly low noise level - whispering mode.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



R410A: Used refrigerant: R410A.



Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



R32: Used refrigerant: R32.



Floor Mode: Natural floor warming effect for greater comfort.



Wifi ready: Optional control of the system via a smartphone.



Preset Mode: Activates individual settings at the touch of a button.



KNX: Optional KNX bus connection.



One Touch Mode: Fully automatic operation adapted to your needs.



Dust filter: Washable filter against coarse contamination.



Timer: Individual programming of on-/off times.



IAQ filter: Fine mesh filter with natural substances.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Week Timer: Up to four settings per day and seven per week.



Plasma filter: Pure Mode: Electrostatic filter system.



Automatic Restart: After a power blackout.



Air ionizer: Negative iones cover polluted particles in the air. Dust, pollen and smoke are neutralized.



8 °C frost protection function: Frost protection for uninhabited rooms.



Self-cleaning function: Usage of condensate water for cleaning.



Louver: Flexible setting of louvers.



Auto Mode: Automatic selection between cooling and heating.



3D Airflow: 6 different airflow patterns in all directions.