TOSHIBA

VERSATILE ALLROUNDER



Highlights

Perfect allrounder with Careflow A +++ for cooling & heating - 3D Airflow (18, 22, 24) Ultra Pure 2.5 filter



Stylish hiwall unit in a seamless matt design. Highest energy efficiency in combination with Ultra-Pure air filter and comfort remote control. 3D- and Careflow- air distribution move the air flow draft-free in the room.

Attractive and economical

- Very high energy efficiency (A +++)
- DC Hybrid inverter technology
- Particularly high efficiency in part load range
- Whisper mode for indoor & outdoor units
- Colored, dimmable LED displays
- Infrared remote control can be used as a cable remote control
- draft-free comfort: 3D Airflow (18, 22, 24)
- intelligent airflow: Hada Careflow

Resource-friendly

- Inverter control minimizes power consumption
- ECO mode
- Air as an energy source in heating mode
- Low-GWP refrigerant R32

Clean ambient air

- Washable dust filters cover the entire heat exchanger
- "Magic Coil" coating of the heat exchanger fins
- Self-cleaning function dries the heat exchanger after the end of operation
- Highly effective Ultra Pure filter of the particle class 2.5 μ

Operation & features

- Comfort infrared remote control included
- Clear & simple operation
- Automatic mode, Hi power, Preset
- Comfort sleep
- Weekly timer with 4 freely programmable settings / day
- 28 time programs per week
- QUIET mode for indoor unit
- SILENT mode for outdoor unit
- 8 ° C frost protection function
- Fireplace mode
- Power Select
- Automatic restart after power failure adjustable
- Optional APP control via smartphone and tablet
- WIFI module can be integrated in the indoor unit
- An indoor unit can be operated by up to 5 users
- Up to 10 indoor units can be controlled by one user
- Several devices can be combined in up to 3 groups / zones
- Child lock
- Multi-Language APP: German, English, Czech, Croatian, Hungarian, Slovenian, Slovak



TOSHIBA

SHORAI EDGE / SET

Indoor unit			RAS-B13J2KVSG-E
Outdoor unit			RAS-13J2AVSG-E
Cooling capacity	kW	*	3,50
Cooling range (minmax.)	kW	*	1,00 - 4,10
Power consumption (min./nom./max.)	kW	*	0,25/0,90/1,12
Pdesign c	kW		3,50
Energy efficiency EER	W/W	*	3,89
Energy efficiency SEER		*	8,60
Energy efficiency class		*	A+++
Outdoor temperature operating range (minmax.)	°C	*	-15/+46
Heating capacity	kW	۲	4,20
Heating range (minmax.)	kW	*	1,00 - 5,30
Power consumption (min./nom./max.)	kW	*	0,20/1,08/1,55
Pdesign h	kW		3,20
Energy efficiency COP	W/W	÷.	3,89
Energy efficiency SCOP		÷.	5,10
Energy efficiency class		÷.	A+++
Outdoor temperature operating range (minmax.)	°C	*	-15/+24

Indoor unit			RAS-B13J2KVSG-E
Sound pressure level (low/med/high)	dB(A)	*	19/23/43
Sound pressure level (low/med/high)	dB(A)	*	19/23/43
Sound power level	dB(A)	*	56
Sound power level	dB(A)	*	56
Airflow	m³/h		732
Dimensions (HxWxD)	mm		293 x 800 x 226
Weight	kg		10

🕸 Cooling 🛛 뵽 Heating

TOSHIBA

SHORAI EDGE / SET

Outdoor unit			RAS-13J2AVSG-E
Power supply	V/Ph+N/Hz		220-240/1/50
Recommended fusing	A		10
Current consumption (max.)	А		8,25
Sound pressure level (low/med/high)	dB(A)	*	46
Sound pressure level (low/med/high)	dB(A)	÷	48
Sound power level	dB(A)	*	56
Sound power level	dB(A)	÷	61
Suction gas pipe diameter	mm (inch)		9,5 (3/8)
iquid pipe diameter	mm (inch)		6,3 (1/4)
Pipe length (min.)	m		2
Pipe length (max.)	m		20
Height difference (max.)	m		12
Airflow	m³/h		1950
Compressor type			Rotary
Refrigerant			R32
Refrigerant charge	kg		0,80
Pre-charged up to	m		15
Added refrigerant charge	g/m		20
Dimensions (HxWxD)	mm		550 x 780 x 290
Weight	kg		30

🕸 Cooling 🔶 Heating

The measuring conditions for this product can be found at http://www.toshiba-klima.at/en/measuring-conditions.html

OSHIBA

TOSHIBA Features - general overview



Energy Label: Energy label A+ to A+++, indicates the power consumption and energy efficiency class.



ErP Ecodesign: All criteria of ECODESIGN-guideline are fulfilled and confirm highest system efficiency.



Hybrid inverter control: Smooth capacity regulation.



Rotary compressor: Reliability and high efficiency.



Twin rotary compressor: Long-lasting, smoothly running and highest efficiency.



R410A: Used refrigerant: R410A.



R32: Used refrigerant: R32.



Wifi ready: Optional control of the system via a smartphone.



KNX: Optional KNX bus connection.



Dust filter: Washable filter against coarse contamination.



IAQ filter: Fine mesh filter with natural substances.



Active carbon-catechin filter: Cleansing filter with enzymes from green tea.



Plasma filter: Pure Mode: Electrostatic filter system.



Air ionizer: Negative iones cover polluted particles in the air. Dust, pollen and smoke are neutralized.



Self-cleaning function: Usage of condensate water for cleaning.



Auto Mode: Automatic selection between cooling and heating.



HI POWER: Particularly strong airflow for quickly reaching the requested temperature.



Auto diagnostic: Check of system for flawless operation.



Eco Mode: Energy saving function.



Quiet Mode: Particularly low noise level - whispering mode.



Comfort Sleep: Gradual increase of temperature by 2 °C until morning.



ব

Power Selection: Capacity regulation and therefore power savings of up to 25, 50 or 75%.



Floor Mode: Natural floor warming effect for greater comfort.



Preset Mode: Activates individual settings at the touch of a button.



One Touch Mode: Fully automatic operation adapted to your needs.



Timer: Individual programming of on-/off times.



Off Timer: Shutdown of the unit at chosen times (30 min to 12 h).



Week Timer: Up to four settings per day and seven per week.



Automatic Restart: After a power blackout.



8 °C frost protection function: Frost protection for uninhabited rooms.



3D ~J||Ŀ> Louver: Flexible setting of louvers.



3D Airflow: 6 different airflow patterns in all directions.



